



# **Furrow Collection Acoustical SPC Click**

*5mm thickness: (Includes a 1mm Hi Mesh EVA Acoustical Pad)*

**Ph: (512) 861-1952**

**Website: [www.advancedflooringc.com](http://www.advancedflooringc.com)**

# Furrow Collection

## 5mm Soundstop Acoustical Click-(Includes 1mm IXPE Pad)

**Size:** 9"x48", 7.25"x48", 6"x36"

**Wear Layer:** 8-mil, 12-mil, 20-mil

**Texture:** Deep Embossed

**Thickness:** 5mm-(Includes a 1mm IXPE Underlayment)

Description	Results
<b>ASTMF1700</b> -(ASTMF2055, ASTMF386, ASTMF410, ASTMF2055, ASTMF1914, ASTMF137, ASTMF2199, ASTMF925, ASTMF2199, ASTMF1515, ASTMF1514, Certificate of Compliance	Pass
<b>ANSIA.137 Dynamic Co-efficient of Friction</b>	Average DCOF .44
<b>ASTME648 Critical Radiant Flux of Floor Covering Systems</b>	Meets or exceeds Class 1 rating as specified in NFPA Life Safety Code 101 and IBC 804.2 Classification
<b>ASTME662 Smoke Density</b>	This sample passes the requirements of 450 or less
<b>ASTMF137 Flexibility of Resilient Flooring Materials</b>	Passes 6mm Mandrel
<b>ASTMF925-Resistant to Chemicals</b>	Pass
<b>ASTMF1514 Measuring Heat Stability-(7 Days)</b>	Test requirements of < 8.0 Delta E were met by the tested samples
<b>ASTMF1515-Measuring Light Stability of Flooring by color change</b>	Test requirements of < 8.0 Delta E were met by the tested samples
<b>ASTMF1914-(Short Term Indentation)</b>	Residual Indentation at 40 lbs-0.015 Inch (7.78%)
<b>ASTMF2199-(Dimensional Stability after exposure to heat)</b>	Length--0.008 Inch per 12 inches (-0.07%) Width-0.013 Inch per 12 inches (-0.11%)
<b>ASTMF2055-(Size, Tolerance)</b>	.016 in/lin ft
<b>ASTMF410-Thickness/Wear Layer</b>	Requirement: Commercial .02, Test Result: .011 inch/.26mm
<b>Certificate of Compliance</b>	Requirement: Max 1/3 of flat surface area/Test Result: Pass
<b>ASTM E90&amp;492 Acoustical Tests</b>	STC61, IIC54, HIIC63

# Furrow Collection



## Soundstop LVT Acoustical SPC Click

### Sizes & Systems

Thickness	Sq Ft Per Carton	Boxes Per Pallet	Sq Ft Per Pallet	Sq Ft Per Container	Pallets Per Container
5mm SPC Click (Includes a 1mm IXPE Acoustical Underlayment)	24	48	1152	23039	20



**Carmella Oak**



**Beech Oak**



**Vienna Grey**



**Vienna Maple**




**Carolina Maple**




**Pierre Oak**



**Iberian Maple**



**Magellan**



**Kenneth Maple**

# Furrow Collection

## Soundstop LVT Acoustical SPC Click



Built-In Acoustical Underlayment

### ASTM Acoustical Results

- STC61
- IIC54
- HIIC63

**\*Tested on a Wood Floor Assembly**

